TECHNICAL DATA

Version 8

AT208 Coloured PVC Dance Floor Advance Gaffa® Tape

General Description

PVC Tape coated with cross – linked solvent based rubber- resin adhesive.

- Wide range of colours
- Water resistant in situ
- Easy unwind
- Easy tear
- Good abrasion resistance
- Conformable to awkward shapes
- Non-corrosive adhesive



Certification to the following standards may be available on request BS EN 60454-3-1/Type 2

Technical Details

Typical Values

Thickness 0.13mm

Breaking Load 25 N/cm

Elongation 170%

Adhesion

Steel 2.3 N/cm

Self 2.0 N/cm

Water Extract

pH 7.2

Conductivity Max. 2mS/m

Flame Retardancy Self Extinguishing

RoHS Compliant Yes

Service Temperature -5°C to +70°C

Application Temperature 0°C to +40°C

Storage Temperature +12°C to +25°C

*standard charge for certificate £25.00



NOTE

Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.





AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.