



COLODash Accent 3

COLODash Accent 3 delivers a tremendous punch of evenly mixed light in a tight 9 degree beam, expandable up to 14 degrees without sacrificing any quality of light. Powered by a 20W RGBA LED, this palm-sized fixture excels at delivering saturated colors and brilliant pastels with a soft, even glow. Variable pulse width modulation allows this fixture to be used for any on camera applications without any issue of flicker and an onboard OLED display effortlessly controls and addresses the fixture via DMX or in a stand-alone mode.



At a Glance

- Quad-color (RGBA) compact LED wash
- Extremely compact with excellent output
- Variable electronic dimmer (0-100%)
- Simple and complex DMX channel profiles with RDM for programming versatility
- Double-bracketed yoke doubles as floor stand
- Easy to use OLED digital display
- Replaceable filter for additional beam angles
- Built-in auto programs recalled via DMX or Master/Slave

Specifications

Optical

- Light Source: 1 LED (quad-color RGBA) 20 W, (950 mA), 50,000 hours life expectancy.
- Installed Optics: 7°
- Beam Angle w/ filter: 14°
- Field Angle w/ filter: 27°
- Beam Angle w/o filter: 9°
- Field Angle w/o filter: 16°
- Lumens: w/o filter: 377 lm
- Lumens: w/ filter: 393 lm
- Illuminance (total) w/ filter: 175 lux @ 5 m
- Illuminance (total) w/o filter: 486 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

Construction / Physical

- Dimensions: 5.94 x 4.92 x 3.13 in (151 x 125 x 80 mm)
- Weight: 2.0 lb (0.9 kg)
- Exterior Color: Black

Control

- Control Protocol: DMX, RDM
- DMX Channels: 4, 7 or 11
- Modes/Personalities: 3 personalities (4, 7, 11)

Certifications / Qualifications

- CE, MET
- IP Rating: IP20, dry location

What's Included

- COLORdash Accent 3

Dynamic Effects

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 25 Hz
- Standalone Color Mixing: Yes
- Dim Modes: 5
- Built-in Automated Programs: Yes

Connections

- Power Connection: Edison plug to hard-wired
- Power Input: Hard-wired
- Data Connectors: 5-pin XLR DMX input and output cable whips
- Cable Length (power): 5 ft (1.5 m)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 18 W, 0.141 A @ 120 V, 60 Hz
- Power and Current: 21 W, 0.098 A @ 208 V, 60 Hz
- Power and Current: 20 W, 0.087 A @ 230 V, 50 Hz

Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- 5-pin DMX Cables
- Color Blending Filters: DF60X1D, DF20D