

Ovation GR-1 IP



SPECIFICATIONS

Dynamic Effects

- Gobos size: B (metal, glass or effect)
- Effects: CW or CCW Rotation, indexing, infinite rotation at variable speeds
- Speed Range: 0.047 – 21 RPM (17° - 7,560° per minute)

FEATURES

- IP65 rated gobo rotator for one single or two counter-rotating gobos
- Fully controllable via the Ovation E-260WW IP control personalities
- Variable speed, bi-directional 0.047-21 RPM (17°- 7,560° per minute) standard rotation
- Fully indexable positioning via DMX
- Dedicated power/control supplied by the Ovation E-260WW IP
- Stepper motor driven for ultra-quiet and super smooth movement without stalling or stuttering

Construction / Physical

- Dimensions: 10.9 x 4.7 x 2.2 in (277.5 x 120.5x 56.9 mm)
- Weight: 2.4 lb (1.2 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast

Connections

- Power Connection: Proprietary 4-pin IP65 input power/data cord (19 in/483 mm)
- Data Connectors: Proprietary 4-pin IP65 input power/data cord (19 in/483 mm)
- Cable Length (power/data): 19 in/483 mm

Control

- Control Protocol: DMX
- DMX Channels: 1

Electrical

- Input Voltage: 24 VDC, 372 mA (via [/products/ovation-](#)

e-260ww-ip/">Ovation E-260WW IP)

Certifications / Qualifications

- CE
- IP Rating: IP65, temporary outdoor/wet use
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

What's Included

- Ovation GR-1 IP
- Power & Data Control Cable