BT-AKKULITE IP

DESCRIPTION

Battery operated outdoor LED-projector, based on 6pcs 10Watt RGBWA-LEDs. The perfect solution for outdoor applications: garden parties, outdoor events, light up trees, plants, walkways, ...

FEATURES

- Battery operated outdoor LED-projector, based on 6pcs 10Watt RGBWA-LEDs to avoid unwanted color shadows.
- Beam angle = 22°
- Projection angle can be adjusted over 25° (vertical to horizontal)
- The perfect solution for outdoor applications: garden parties, outdoor events, light up trees, plants, walkways, ...
- +/-10hrs use in fading mode on a fully charged battery!
- Each projector is equipped with a wireless transceiver module (transmitter and receiver) which is 100% compatible with the W-DMX G4-protocol from "Wireless Solution Sweden".
- Projector can still be used with empty battery: just connect it to the mains!
- Very smooth RGBWA color changes thanks to high freq. dimming electronics
- The internal battery charger charges the battery while the projector is working on mains power.
- Different working modes:
 - Standalone: custom colors selectable or automatic and beat synchronized color changes
 - Master/slave mode: wonderful preprogrammed, music synchronized lightshows.
 - DMX-controlled : cabled and wireless. (5 modes : 4-5-9-10 channels, LEDCON-02 Mk2)
 - Controlled by a small JB Systems LEDCON-02 Mk2 or LEDCON-XL controller
 - Controlled by wireless IR remote control
- Weatherproof mains input (Neutrik PowerCon® compatible).
- Weatherproof 3-pin XLR input and output connectors
- NOTE: this product has IP65 rating while used for nonpermanent outdoor installation and under normal conditions (not exposed to seawater).









www.briteq-lighting.com | https://www.facebook.com/Briteq

TECHNICAL SPECIFICATIONS

General: Series No

General : Dimensions (cm) $18 \times 15 \times 19,8 \text{ cm}$

General: Weight (kg) 4.

General : Powerinput AC 100 - 240V, 50/60Hz, Battery

General: Energy Label No
General: Power consumption W 60
General: Color black
General: Display LCD
General: IP rating outdoor
Control: manual Yes
Control: Master/Slave Yes
Control: SMART-DMX No

Control : Standalone automatic, sound, fixed

Control: Type included remote
Control: programmable
Control: upgradable software
Control: maximum DMX channels
10

Control: upgradable software

Control: maximum DMX channels

Light: lamp socket

Light: lamp

LED

Light : colorsRed, Green, Blue, White, Amber,

RGB, RGBW, RGBWA

Light: mix colors

Light: min. refresh rate (kHz)

No
No

Light: max. refresh rate (kHz)

No
3 pin XLR, wireless DMX, wifi,

Payer Con @ or compatible

PowerCon® or compatible 3 pin XLR, wifi, PowerCon® or

Connections : output compatible

Brand BRITEQ

EANCode 5420025651356

RED (627nm) GREEN (522nm) BLUE(458nm) WHITE (6500K) AMBER (1740K) LUX (full on)	1950 2750 495 2600 1300 8160	488 688 124 650 325 2040	217 306 55 289 145 907	122 172 31 163 81 510	78 110 20 104 52 326	55 77 14 72 36 227
BT-AKKULIT	E IP					
BEAM Ø (cm	1 0.39	2 0.78	3 1.17	4 1.56	5 1.94	6 2.33





