

# AMP200.2 Mk2

## DESCRIPTION

Power amplifier 2x 250Wrms / 4ohm

## FEATURES

- › Professional 2-channel CLASS-D power amplifier
- › This Mk2 version was completely reworked internally for better reliability and higher power
- › Extremely compact 19" housing, height only 1U (44mm)
- › Lightweight design based on soft start switch mode power supply
- › 3 amplifier modes: stereo, mono and bridge
- › Power stereo:
  - › 2x 250Wrms @ 4Ω
  - › 2x 130Wrms @ 8Ω
- › Power bridge:
  - › 1x 500Wrms @ 8Ω
- › Very efficient cooling, using temperature controlled fans.
- › Peak limiter prevents signal distortion
- › Switchable 75Hz / -24dB low cut filter
- › Adjustable input sensitivity: 0,775V ~ 1,0V ~ 1,44V
- › Ground lift switch
- › A plastic cover (included) can be installed to prevent unauthorized persons from changing the input levels
- › DC fault + high temperature + overload and short circuit protections
- › Balanced XLR-inputs & jack-outputs: daisy chaining of several amplifiers
- › 3 Speakon® outputs: left + right channels + bridge



## TECHNICAL SPECIFICATIONS

<b>General : Dimensions (cm)</b>	48.3 x 24 x 4.4
<b>General : Weight (kg)</b>	4
<b>General : Color</b>	black
<b>General : Powerinput</b>	AC 240V, 50Hz
<b>General : Energy Label</b>	No
<b>General : Display</b>	No
<b>General : Fixation</b>	19" rack mountable
<b>General : RU</b>	1U
<b>General : IP rating</b>	indoor
<b>Audio : frequency range</b>	20 Hz - 20000 Hz
<b>Audio : S/N ratio (&gt; dB)</b>	100
<b>Audio : max. output channels</b>	2
<b>Audio : Wrms 4Ω stereo, per channel</b>	250
<b>Audio : Wrms 8Ω stereo, per channel</b>	130
<b>Audio : Wrms 8Ω bridge</b>	500
<b>Audio : functions</b>	adjustable crossover, bridge mode, limiter
<b>Connections : input</b>	3 pin XLR, IEC
<b>Connections : output</b>	3 pin XLR, speakon
<b>Brand</b>	JB SYSTEMS
<b>EANCode</b>	5420025681285
<b>SKU</b>	B08128



AVOID TAMPERING WITH AUDIO SETTINGS



YOUR DEALER

