

PCBB³ As with PCBB2 eliminates hum problems when connecting audio from your presentation PC. Hum can happen anywhere. You don't have to be running your audio signal a long distance. Power supplies, lighting and all sorts of equipment can cause noise that is picked up by your audio input cables. With the no compromise bandwidth of 20Hz to 20kHz. In addition PCBB3 comes with a plug and socket input lead to aid replacement when damaged.

- Stereo/Mono selection switch.
- 20Hz to 20kHz bandwidth.
- 35dB pad switch allows audio to be connected to a desk on either Line or Mic inputs.
- Earth (Ground) isolation ensures that ground loops are easily defeated.
- Left/Right XLR output connectors are standard for live events audio.
- Compact size.
- No power required (passive) - always ready to go
- Captive lead ensures easy connection every time now with plug and socket to aid service.



The 'Hum' Eliminator

3 Year Limited Factory Warranty

Specifications

Power:

None required

Signals:

Typical input 700mVp-p unbalanced stereo audio
Bandwidth 20Hz-20kHz Signal levels depend on input level and output impedance.

Control Switches:

Output Pad from -2dB/ -35dB
Earth (Ground) Lift
Stereo to Mono

Connections:

Input 3.5mm mini stereo jack with internal plug and socket to help servicing of these units ~ requires dismantling.
Output 2 x male XLR

Dimensions mm (inch):

D x W x H
71 (2 8/10") x 64 (2 1/2") x 40 (1 6/10")
Captive lead length 1.8m (6ft)

Weight each

218g (8oz)

Customer Supplied Parts:

XLR cables to suit



Note XLR cables and not included as standard.

Interspace Industries

Unit 1F Tewin Court, Tewin Road, Welwyn Garden City, Hertfordshire, AL7 1AU, UK

call: +44 (0) 1462 600 101 email: moreinfo@interspaceind.com web: www.interspaceind.com

Disclaimer: Whilst all care is taken to ensure accuracy, Interspace Industries Ltd accepts no responsibility for any errors or omissions, whether implied or otherwise interpreted. All specifications subject to change without notice.

